Safety Data Sheet

Section 1 - Identification



Pale Yellow / 6500 ¹
Cadmium Primrose / 6505 ²
Bismuth Vanadate Yellow / 6510 Permanent Yellow / 6515 ¹
Cadmium Yellow Medium / 6520 ²
Permanent Yellow Deep / 6525
Cadmium Orange / 6530 ²
Medium Orange / 6535
Light Orange / 6540
Cadmium Red Light / 6545 ²
Naphthol Red Light / 6550
Pyrrole Red / 6555
Quinacridone Red / 6560
Cadmium Red Dark / 6565 ²
Naphthol Pink / 6570

Light Magenta / 6575 Crimson / 6580 Quinacridone Magenta / 6585 Light Violet / 6590 Red Violet / 6595 Dioxazine Violet Deep / 6600 Blue Violet / 6605 Ultramarine Blue / 6610 Light Ultramarine Blue / 6615 Phthalo Blue (Green Shade) / 6620 Light Phthalo Blue / 6635 Cerulean Blue Hue / 6630 Medium Phthalo Blue / 6635 Turquoise / 6640 Cobalt Teal / 6645 Phthalo Green (Blue Shade) / 6650 Light Phthalo Green / 6655 Permanent Green / 6660 Dark Green / 6665 Light Green Yellow / 6670 Yellow Green / 6675 Olive / 6680 ¹ Titan Green Pale / 6685 Titan Buff / 6690 Naples Yellow Deep / 6695 Yellow Oxide / 6700 Mars Yellow Deep / 6705 Titan Mars Pale / 6710 Titan Violet Pale / 6715 Red Oxide / 6720

Phone: (607)847-6154

Cobalt Blue / 6725
Burnt Sienna / 6730 ³
Burnt Umber / 6735 ³.5
Raw Umber / 6740 ³.4.5
Black / 6745 ⁴
Payne's Gray / 6750 ⁴
Titanium White / 6755
N5 Neutral Gray / 6760 ⁴
N8 Neutral Gray / 6760 ⁴
N8 Neutral Gray / 6760 ⁵
Fluorescent Yellow / 6770 ⁶
Fluorescent Crange / 6785 ⁶
Fluorescent Pink / 6785 ⁶
Fluorescent Pink / 6785 ⁶
Fluorescent Violet / 6790 ⁶
Fluorescent Green / 6795 ⁶

1, 2, 3, 4, 5, 6 Denotes Additional Information Found in Section 15

In US and Canada only: (800)959-6543

GOLDEN ARTIST COLORS, INC.

188 BELL ROAD NEW BERLIN, NY 13411

Product Use: Artist's Paint

Prepared by: Regulatory Department

roparda by. regulatory Bopartmont

Not recommended for: Use by children

Section 2 - Hazards Identification

GHS Ratings:

There are no GHS ratings that apply to this product at this time

GHS Hazards

There are no GHS hazards that apply to this product at this time

GHS Precautions

There are no GHS precautions that apply to this product at this time

Section 3 - Hazardous Composition

Chemical Name	CAS number	Weight Concentration %
Not Applicable		_

Section 4 - First Aid

Inhalation: Remove subject to fresh air. Small levels of Ammonium Hydroxide (28%) may be present. Give artificial respiration if breathing has stopped. Seek medical attention.

Eye: Flush with water for 15 minutes. Remove contact lenses, if present and easy to do so. If symptoms develop and persist seek medical attention.

Skin: Wash with soap and water. Remove contaminated clothing. Seek medical attention for irritation.

Ingestion: If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS! Do not induce vomiting. Seek medical attention IMMEDIATELY.

Section 5 - Fire Fighting

Flash Point: 100 C (212 F)

LEL: N/A UEL: N/A

Extinguishing Media: Water, Foam, Carbon Dioxide, Dry Chemical, Powder. Do NOT use high pressure Water

SDS for: SoFlat Matte Acrylics Page 1 of 4

Spray, as this may spread the fire.

Unusual Fire and Explosion Hazards: Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/ or fumes may generate during combustion or decomposition.

Hazardous Byproducts: Combustion will yield oxides of carbon and nitrogen, as well as, monomer fume. See Section 10 for additional information.

Fire Fighting Procedures: Move containers promptly out of fire zone. If removal is impossible, keep containers cool with water spray. Remain upwind and avoid breathing smoke or fumes.

Special Precautions: Wear self-contained breathing apparatus and full protective gear.

Section 6 - Release

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See Section - 8 Exposure Control for recommendations. If exposed to material during clean-up operations, see Section 4 - First Aid for actions to follow.

Environmental precautions: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and clean-up: Evacuate personnel to safe areas. Ventilate the area to dissipate vapor. Floor may be slippery; use care to avoid falling. Soak up spills with inert absorbent material. Sweep up and collect in suitable container for disposal. Avoid breathing vapor.

Section 7 - Handling

Precautions and safe handling: Use only in well-ventilated areas. Avoid inhalation of vapors/spray and contact with skin and eyes. Wear appropriate personal protective equipment. Read label before use.

Conditions for safe storage: Store in a cool, well-ventilated place. Keep out of the reach of children.

Section 8 - Exposure Control			
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Ammonium Hydroxide (28%) 1336-21-6	TWA 35 mg/m3 PEL, 50 ppm	TWA 18 mg/m3 TLV, 25ppm	Not Established

Engineering Controls: Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of possible vapor. Provide easy access to water supply, eye wash or emergency shower.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and work clothes should be kept separate.

Personal Protective Equipment: None required under normal use. For techniques requiring continual hand exposure, gloves are recommended. Safety glasses or goggles recommended when spraying.

Section 9 - Properties

Properties listed are typical and not to be used as a specification.

Appearance: Liquid	Odor: Slight Amine
Vapor Pressure: Not available	Odor threshold: Not available

SDS for: SoFlat Matte Acrylics Page 2 of 4

Printed: 1/31/2023 at 10:53:21AM

Vapor Density: Not available

Density: 1.05 – 1.40

Freezing point: Not available

Boiling range: Not available

Evaporation rate: Not available

Explosive Limits: Not available

Auto ignition temperature: Not available

Viscosity: 1500 - 2300 cP

pH: 8.7 - 9.3

Melting point: Not applicable

Solubility: Miscible

Flash point: 100°C, 212°F

Flammability: Not applicable

Partition coefficient Not available

(n-octanol/water):

Decomposition temperature: Not available

Section 10 - Reactivity

Under normal conditions this mixture is considered to be:

Materials that are known to be incompatible with this mixture and should be avoided, if applicable:

Acids, high temperatures (see below)

Risk of hazardous decomposition:

Red Violet, Blue Violet, Ultramarine Blue and Payne's Gray – Contact with acids liberates Hydrogen Sulphide (H₂S) gas, at temperatures above 400 C in the presence of air an exothermic reaction can occur with the liberation of Sulphur Dioxide (SO₂) gas.

Cadmiums – May react with strong acids yielding toxic/flammable Hydrogen Sulphide (H₂S) gas, fire/thermal decomposition can produce hazardous fumes (Cadmium Oxide, Selenium Dioxide) and gases (Sulfur Dioxide).

Hazardous polymerization will not occur.

Section 11 - Toxicology

Mixture Toxicity: This mixture as a whole has not been tested to determine its toxicity.

Possible routes of entry or exposure:

Not Applicable

Possible target organs of exposure to this mixture:

Not Available

Effects of Overexposure

Not Available

Carcinogenicity: This mixture as a whole has not been tested to determine its carcinogenic properties.

Section 12 - Ecological Toxicity

Ecotoxicity: This mixture as a whole has not been tested to determine its ecological toxicity.

Section 13 - Disposal

Disposal Instructions: Dispose as per local regulations. It is best to use all material, rather than dispose of it. If necessary, dispose of as latex paint. Cadmium pigmented paints should be treated as hazardous waste.

SDS for: SoFlat Matte Acrylics Page 3 of 4

Printed: 1/31/2023 at 10:53:21AM

Section 14 - Transport

Agency	Proper Shipping Name	UN Number	Packing	<u>Hazard Class</u>
Agency	Proper Snipping Name	UN NUMBER	Packing	IIGA

DOT Not Regulated IATA Not Regulated IMDG Not Regulated

Section 15 - Regulatory

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

CAS#	Description	<u> Hazard</u>
Various	Nickel Compound ¹	Carcinogen
Various	Cadmium Compound ²	Carcinogen
14808-60-7	Quartz (Crystalline Silica) ³	Carcinogen
1333-86-4	Carbon Black ⁴	Carcinogen
Various	Lead and Lead Compounds ⁵	Carcinogen/Reproductive Toxin
50-00-0	Formaldehyde ⁶	Carcinogen

<u>Country</u>	Regulation	All Components Listed
AUSTRALIA	AICS- Australian Inventory of Chemical Substances	Yes
CANADA	Domestic Substances List (DSL) and Non-Domestic	Yes
EUROPE	European Inventory of Existing Commercial Chemical	Yes
EUROPE	European List of Notified Chemical Substances	No
JAPAN	Inventory of Existing and New Chemical Substances	No
CHINA	Inventory of Existing Chemical Substances in China	Yes
KOREA	Korean Existing Chemicals Inventory (KECI)	Yes
NEW ZEALAND	New Zealand Inventory of Chemicals (NZIoC)	Yes
PHILIPPINES	Philippine Inventory of Chemicals and Chemical	Yes
USA	Active-Toxic Substances Control Act (TSCA) Inventory	Yes

Section 16 - Other Information

While Golden Artist Colors, Inc. believes the data set forth herein is accurate as of the date hereof, Golden Artist Colors, Inc. makes no warranty with respect to the accuracy of this data and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation, and verification.

Date revised: 2023-01-31 Reviewer Revision 2

Date Prepared: 1/31/2023

SDS for: SoFlat Matte Acrylics Page 4 of 4