Safety Data Sheet

Section 1 - Identification

DEN COLORS® MSA

GLOSS MSA VARNISH w/UVLS / 7770 SATIN MSA VARNISH w/UVLS / 7775 MATTE MSA VARNISH w/UVLS / 7780

GOLDEN ARTIST COLORS, INC. 188 BELL ROAD NEW BERLIN, NY 13411

Phone: (607)847-6154 In US and Canada only: (800)959-6543

Prepared by: Regulatory Department

Product Use: Artist's Material

Not recommended for: Use by children

Section 2 - Hazards Identification

GHS Ratings:

Flammable liquid Skin corrosion/irritation	4 3	Flash point >= 60°C (140°F) and <= 93°C (200°F) Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Serious eye damage/eye irritation	2B	Mild eye irritant: Subcategory 2B, Reversible in 7 days
Skin sensitization	1	Skin sensitizer
Carcinogenicity	2	Limited evidence of human or animal carcinogenicity

GHS Hazards

H227	Combustible liquid
H316	Causes mild skin irritation
H317	May cause an allergic skin reaction
H320	Causes eye irritation
H351	Suspected of causing cancer

GHS Precautions

F	P201	Obtain special instructions before use
F	202	Do not handle until all safety precautions have been read and understood
F	P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
F	P235	Keep cool
F	P261	Avoid breathing dust/fume/gas/mist/vapors/spray
F	P264	Wash hands with soap and water thoroughly after handling
F	P272	Contaminated work clothing should not be allowed out of the workplace
F	280	Wear protective gloves/protective clothing/eye protection/face protection
F	P281	Use personal protective equipment as required
F	P321	Specific treatment, see Section 4
F	- 363	Wash contaminated clothing before reuse
F	P302+P352	IF ON SKIN: Wash with soap and water
F	P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
F	P308+P313	IF exposed or concerned: Get medical advice/attention
F	P332+P313	If skin irritation occurs: Get medical advice/attention
F	P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
F	P337+P313	If eye irritation persists, get medical advice/attention
F	P370+P378	In case of fire: Use for extinction
F	> 405	Store locked up
F	P403+P235	Store in a well ventilated place. Keep cool

Signal Word: Warning



Section 3 - Hazardous Composition

Chemical Name	CAS number	Weight Concentration %
Petroleum distillate hydrotreated light	64742-47-8	40.00% - < 50.00%
Solvent Naptha, Petroleum, Heavy Aromatic	64742-94-5	20.00% - < 30.00%
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl)	41556-26-7	0.10% - < 1.00%
Methyl1,2,2,6,6-pentamethyl-4-piperidinyl)	82919-37-7	0.10% - < 1.00%
Naphthalene ⁽¹⁾	91-20-3	0.10% - < 0.30%

(1) Napthalene - WARNING: This product contains a chemical known to the State of California to cause cancer.

Section 4 - First Aid

Inhalation: Remove subject to fresh air. Give artificial respiration if breathing has stopped. Seek medical attention.

Eye: Flush with water for 15 minutes. Remove contact lenses, if present and easy to do so. If symptoms develop and persist seek medical attention.

Skin: Wash with soap and water. Remove contaminated clothing. Seek medical attention for irritation.

Ingestion: If swallowed, dilute by giving 2 or more glasses of water to drink ONLY IF CONSCIOUS! Do not induce vomiting. Seek medical attention IMMEDIATELY.

Section 5 - Fire Fighting

Flash Point: 64 C (147 F) LEL: N/A

UEL: N/A

Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical, Powder. Do NOT use high pressure Water Spray, as this will spread the fire.

Unusual Fire and Explosion Hazards: Vapors can travel to s source of ignition and flash back. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/ or fumes may generate during combustion or decomposition.

Hazardous Byproducts: Combustion will yield oxides of carbon and nitrogen, as well as, monomer fume.

Fire Fighting Procedures: Move containers promptly out of fire zone. If removal is impossible, keep containers cool with water spray. Remain upwind and avoid breathing smoke or fumes.

Special Precautions: Wear self-contained breathing apparatus and full protective gear.

Section 6 - Release

Personal precautions, protective equipment and emergency procedures: Appropriate protective equipment must be worn when handling a spill of this material. See Section - 8 Exposure Control for recommendations. If

exposed to material during clean-up operations, see Section 4 - First Aid for actions to follow.

Environmental precautions: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods and materials for containment and clean-up: Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area to dissipate vapor. Floor may be slippery; use care to avoid falling. Soak up spills with inert absorbent material. Sweep up and collect in suitable container for disposal. Avoid breathing vapor.

Section 7 - Handling

Precautions and safe handling: Use only in well-ventilated areas. Avoid inhalation of vapors/spray and contact with skin and eyes. Wear appropriate personal protective equipment. The mixture is flammable, and heating may generate vapors which may form explosive vapor/air mixtures. Do not smoke or use near other sources of ignition. Read label before use.

Conditions for safe storage: Keep away from heat, sparks and open flame. Store in a cool, well-ventilated place. Keep out of the reach of children.

Section 8 - Exposure Control				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Petroleum distillate hydrotreated light 64742-47-8	PEL 5mg/m3 TWA 5mg/m3	TWA 10mg/m3	Not Established	
Solvent Naptha, Petroleum, Heavy Aromatic 64742-94-5	PEL 500 PPM	Not Established	Not Established	
Bis(1,2,2,6,6-pentamethyl-4-p iperidinyl) 41556-26-7	Not Established	Not Established	Not Established	
Methyl1,2,2,6,6-pentamethyl- 4-piperidinyl) 82919-37-7	Not Established	Not Established	Not Established	
Naphthalene 91-20-3	TWA 10ppm/50 mg/m3 ST 15ppm/ 75 mg/m3	TWA 10 ppm SKIN	Not Established	

Engineering Controls: Use explosion proof ventilation equipment. Provide adequate ventilation. Observe Occupational Exposure Limits and minimize the risk of inhalation of possible vapor. Provide easy access to water supply, eye wash or emergency shower.

General Hygiene Considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Private clothes and work clothes should be kept separate.

Personal Protective Equipment: Wear approved safety glasses or goggles. Wear solvent-resistant gloves. Be aware that liquid may penetrate the gloves, suitable gloves can be recommended by the glove supplier.

Section 9 - Properties

Properties listed are typical and not to be used as a specification.

Appearance: Liquid Vapor Pressure: Not available Vapor Density: Not available Density: 0.85 – 0.95 Odor: Solvent Odor threshold: Not available pH: Not applicable Melting point: Not applicable Freezing point: Not available Boiling range: Not available Evaporation rate: Not available

Explosive Limits: Not available

Auto ignition temperature: Not available Viscosity: 700 - 1400 cP Solubility: Not soluble

Flash point: 64°C, 147°F

Flammability: Not applicable

Partition coefficient Not available (n-octanol/water):

Decomposition temperature: Not available

Section 10 - Reactivity

Under normal conditions this mixture is considered to be:

STABLE

Materials that are known to be incompatible with this mixture and should be avoided, if applicable:

Not Applicable

Risk of hazardous decomposition:

Not Applicable

Hazardous polymerization will not occur.

Section 11 - Toxicology

Mixture Toxicity

Oral Toxicity LD50: 3,779mg/kg Inhalation Toxicity LC50: 56mg/L

Component Toxicity

Noty	
Petroleum distillate hydrotreated light Oral LD50: 2,000 mg/kg (RAT)	
Solvent Naptha, Petroleum, Heavy Aromatic Dermal LD50: 3,160 mg/kg (RABBIT)	
Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) Oral LD50: 2,615 mg/kg (RAT)	
Naphthalene Oral LD50: 490 mg/kg (RAT) Dermal LD50: 2,500 mg/kg (RAT)	
	Petroleum distillate hydrotreated light Oral LD50: 2,000 mg/kg (RAT) Solvent Naptha, Petroleum, Heavy Aromatic Dermal LD50: 3,160 mg/kg (RABBIT) Bis(1,2,2,6,6-pentamethyl-4-piperidinyl) Oral LD50: 2,615 mg/kg (RAT) Naphthalene

Possible routes of entry or exposure:

Inhalation Skin Contact Eye Contact Ingestion

Possible target organs of exposure to this mixture:EyesLungsGI TractRespiratory System

Effects of Overexposure

Carcinogenicity: This mixture as a whole has not been tested to determine its carcinogenic properties. The components of this mixture that are reported as possible or known carcinogens are as follows:

CAS Number	Description	<u>% Weight</u>	Carcinogen Rating
91-20-3	Naphthalene	0.1% - < 0.3%	Naphthalene: Caused cancer in

Naphthalene: Caused cancer in laboratory animal studies. The relevance of these findings to humans is uncertain.

Acute Toxicity: May cause central nervous system effects.

Section 12 - Ecological Toxicity

Ecotoxicity: This mixture as a whole has not been tested to determine its ecological toxicity. The components of this mixture with documented ecological data are as follows:

Component Ecotoxicity Petroleum distillate hydrotreated light	LC50 Oncorhynchus mykiss 2.4 mg/l 96h LC50 pimephales promelas 45 mg/l 96h LC50 Lepomis macrochirus 2.2 mg/l 96h LC50 Den-dronereides heteropoda 4720 mg/l 96h
Solvent Naptha, Petroleum, Heavy Aromatic	LC50, RAINBOW TROUT, 96h, 3.6 mg/l EC50, WATER FLEA, 48h, 1.1 mg/l EC50, GREEN ALGAE, 72h 7.2 mg/l
Bis(1,2,2,6,6-pentamethyl-4-piperid inyl)	LC50 Lepomis Macrochirus 1 mg/l 96h EC50 Water Flea 20 mg/l 48h
Naphthalene	LC50, RAINBOW TROUT, 96h, 0.11 mg/l EC50, WATER FLEA, 48h, 1.6 - 24.1 mg/l

Section 13 - Disposal

Disposal Instructions: Contract with a disposal operator licensed by the Law on Disposal and Cleaning. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Must be incinerated in a suitable incineration plant holding a permit delivered by the competent authorities. Do not discharge into drains, water courses or onto the ground. Dispose of contents/container in accordance with local/regional/national/international regulations.

Section 14 - Transport				
ChemTel Co	ontract #MIS0002572 Phone: (888)255-3924			
<u>Agency</u> DOT	Proper Shipping Name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naptha (petroleum), heavy arom.)	<u>UN Number</u> UN3082	<u>Packing</u> III	Hazard Class 9
ΙΑΤΑ	Marine Pollutant ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naptha (petroleum), heavy arom.)	UN3082	III	9
IMDG	Environmental Hazards ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Distillates (petroleum), hydrotreated light, Solvent naptha (petroleum), heavy arom.)	UN3082	III	9
	Marine Pollutant			

Section 15 - Regulatory

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition

65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

91-20-3 Naphthalene Carcinogen

<u>Country</u>	Regulation	All Components Listed
AUSTRALIA	AICS- Australian Inventory of Chemical Substances	Yes
CANADA	Domestic Substances List (DSL) and Non-Domestic	Yes
EUROPE	European Inventory of Existing Commercial Chemical	Yes
EUROPE	European List of Notified Chemical Substances	No
JAPAN	Inventory of Existing and New Chemical Substances	No
CHINA	Inventory of Existing Chemical Substances in China	Yes
KOREA	Korean Existing Chemicals Inventory (KECI)	Yes
NEW ZEALAND	New Zealand Inventory of Chemicals (NZIoC)	Yes
PHILIPPINES	Philippine Inventory of Chemicals and Chemical	Yes
USA	Active-Toxic Substances Control Act (TSCA) Inventory	Yes

Section 16 - Other Information

While Golden Artist Colors, Inc. believes the data set forth herein is accurate as of the date hereof, Golden Artist Colors, Inc. makes no warranty with respect to the accuracy of this data and expressly disclaims all liability for reliance thereon. Such data is offered solely for your consideration, investigation, and verification.

Date revised: 2024-03-05 Date Prepared: 3/5/2024 **Reviewer Revision 2**